

SC71701Q, Single-Channel Automotive Antenna LDO with Current Sense

1 Descriptions

The SC71701Q is a single-channel low-dropout regulator (LDO) family, designed to operate for a wide input voltage range from 4.5-V to 36-V (40-V load dump capability). The LDO family is suitable to supply automotive active antenna, camera modules and microphone applications through coax cables with 400-mA current capability per channel.

The SC71701Q is designed to indicate full diagnostics through current sense and error pins to MCU. Therefore, current sense is multiplexed to report a proportional analog output to the sensed load current and provide fault indications without external calibrations. The current limit of individual channel is adjustable by a resistor on ILIM pin.

Implementing Back-to-Back (B2B) FET structure, SC71701Q is able to protect against reverse current and reverse battery polarity failures without extra input diode. The LDO also offers thermal shutdown (TSD) and output short-to-battery (STB) protection. An internal inductive clamp diode is integrated for each channel to protect the device during shutdown with a long inductive cable on output.

The SC71701Q is available in HTSSOP-16 package.

3 Applications

Automotive active antenna power

Automotive camera module and sensor power

Automotive microphone power

4 Device Information

2 Features

- AEC-Q100 qualified for automotive applications:
 - Temperature grade 1: T_A range: -40°C to 125 °C
- 4.5-V to 36-V wide input voltage range, 40-V load dump capability
- Excellent output performance
 - 1.5-V to 22-V adjustable output voltage range
 - Up to 400-mA current capability per channel
- Single and dual-channel LDO in same package
- Adjustable current limit
- High current sense accuracy to detect very light load condition: ±10% at 5-mA load and ±50% at 1-mA load
- High Power Supply Rejection Ratio (PSRR): Typical 70dB at 100-Hz
- 500-mV (max) dropout voltage at 100-mA load
- Power switch mode when FB is short to GND
- Full diagnostics and integrated protection for robust design
 - Input undervoltage lockout (UVLO)
 - Reverse battery polarity protection
 - Reverse current protection (RCP)
 - Output short-to-battery (STB) protection
 - Output inductive load clamp
 - Output short-circuit protection (SCP)
 - Thermal shutdown (TSD)
- HTSSOP-16 Package with thermal pad
- SC71701Q has same package with
 - SC71702Q (Dual channel)

ORDER NUMBER	CHANNEL	Fault Logic	PACKAGE	BODY SIZE
SC71701QSJER	Single channel	Latch-off	HTSSOP-16	5mm x 6.4mm x 1.2mm
SC71701AQSJER	Single channel	Auto-retry	HTSSOP-16	5mm x 6.4mm x 1.2mm
SC71701DQSJER	Single channel	Latch-off	HTSSOP-16	5mm x 6.4mm x 1.2mm
SC71701EQSJER	Single channel	Auto-retry	HTSSOP-16	5mm x 6.4mm x 1.2mm



5 Revision History

Revision	Date	Page(s) changed	Changes Description
V1.0.0	2023/8	/	Initial Version
V1.0.1	2024/1	16	Updated Auto-retry Logic Description
V1.0.2	2025/9	25	Updated Example Stencil Design
V1.0.3	2025/12	1	Updated Device Information

6 Typical Application Circuit





Figure 6-1 Typical Application Circuit



7 Terminal Configuration and Functions

TOP VIEW



Pin Map of SC71701Q

TERMINAL		I/O	DESCRIPTION
PIN NUMBER	SINGLE-CHANNEL		
1	VIN	I	Power supply input.
2	EN	I	Active high enable input for OUT. LDO is enabled when EN goes high, and is disabled when EN goes low. This pin has internal pull-down to GND. This pin can be short to GND or floating if not used.
3	NC	-	Not connected. Connect this pin to GND or leave floating
4	VCC	O	Internal 4.5-V regulator output. Used to supply internal control circuitry. Connect a 1- μ F ceramic capacitor between VCC and GND.
5	CS	O	Output of sensed load current. When $\overline{\text{CS_EN}}$ is set to low, CS's output current is proportional to current through OUT. A resistor should be connected between CS and GND to get appropriate CS output voltage level. A 1- μ F ceramic capacitor from CS and GND is needed for compensation of current sense loop. This pin can be short to GND or floating if not used.
6	NC	-	Not connected. Connect this pin to GND or leave floating
7	NC	-	Not connected. Connect this pin to GND or leave floating
8	$\overline{\text{CS_EN}}$	I	The $\overline{\text{CS_EN}}$ enables and disables the current sense multiplexing feature. This pin is active low. When not used, short this pin to GND or leave it floating.
9	$\overline{\text{ERR}}$	O	This pin is an Open-drain (OD) fault indicator. Used to report faults. This pin can be connected to GND or floating if not used.
10	ILIM	I	Connect a resistor between this pin to GND to program current limit for LDO. Short this pin to GND will set current limit to internal current limit.
11	NC	-	Not connected. Connect this pin to GND or leave floating
12	GND	G	Ground reference. Connect this pin directly to the thermal PAD on PCB.



13	NC	-	Not connected. Connect this pin to GND or leave floating
14	NC	-	Not connected. Connect this pin to GND or leave floating
15	FB	I	Feedback input for LDO's output voltage setting. This pin can be connected to GND for current limited power switch mode operation.
16	OUT	O	Output of LDO



8 Specifications

8.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted) ⁽¹⁾

PARAMETER		MIN	MAX	Unit
Voltage range at terminals ⁽²⁾	Unregulated input, VIN to GND	-40	40	V
	EN to GND	-0.3	40	V
	OUT to GND ⁽³⁾	-0.3	40	V
	FB to GND	-0.3	40	V
	VCC	-0.3	6	V
	CS to GND	-0.3	VCC+0.3	V
	ILIM, CS_EN, ERR	-0.3	7	V
T _J	Operating junction temperature range	-40	150	°C
T _A	IC operating ambient temperature range	-40	125	°C
T _{stg}	Storage temperature range	-65	150	°C

- (1) Stresses beyond those listed under *absolute maximum ratings* may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under *recommended operating conditions* is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) All voltage values are with respect to network ground terminal.
- (3) There is an internal diode connecting between the OUT and GND pin with 400mA DC current capability for inductive clamp protection.

8.2 Handling Ratings

PARAMETER	DEFINITION	MIN	MAX	UNIT
ESD ⁽¹⁾	Human body model (HBM) ESD stress voltage ⁽²⁾ , per AEC Q100-002	-2	2	kV
	Charged device model (CDM) ESD stress voltage ⁽³⁾ , per AEC Q100-011	-750	750	V

- (1) Electrostatic discharge (ESD) to measure device sensitivity and immunity to damage caused by assembly line electrostatic discharges into the device.
- (2) Level listed above is the passing level per ANSI, ESDA, and JEDEC JS-001. JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.
- (3) Level listed above is the passing level per EIA-JEDEC JESD22-C101. JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.



8.3 Recommended Operating Conditions

PARAMETER		MIN	TYP	MAX	UNIT
V_{IN}	Input voltage range	4.5		36	V
V_{OUT}	Output voltage. Regulated LDO mode	1.5		22	V
	Output voltage. Power switch mode	1.5		36	V
C_{OUT}	Output capacitance range for loop stability	2.2		100	μF
$C_{OUT(ESR)}$	Output capacitor's ESR range for stability	0		5	Ω
T_J	Operating junction temperature range	-40		150	$^{\circ}C$
T_A	Operating ambient temperature range	-40		125	$^{\circ}C$

8.4 Thermal Information

THERMAL RESISTANCE ⁽¹⁾		HTSSOP-16	UNIT
Θ_{JA}	Junction to ambient thermal resistance	41	$^{\circ}C/W$
$\Theta_{JC(top)}$	Junction to case (top) thermal resistance	26	$^{\circ}C/W$
Θ_{JB}	Junction-to-board thermal resistance	19.7	$^{\circ}C/W$
Ψ_{JT}	Junction-to-top characterization parameter	1.3	$^{\circ}C/W$
Ψ_{JB}	Junction-to-board characterization parameter	20.1	$^{\circ}C/W$
$\Theta_{JC(bot)}$	Junction to case (bottom) thermal resistance	3	$^{\circ}C/W$

(1) Measured on JESD51-7, 4-layer PCB.

8.5 Electrical Characteristics

$T_J = -40^{\circ}C$ to $150^{\circ}C$, $V_{IN} = 14V$. Typical value is tested at $T_J = +25^{\circ}C$, unless otherwise noted.

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
SUPPLY VOLTAGE						
V_{IN}	Input voltage range		4.5		36	V
V_{IN_UVLO}	Under voltage lockout threshold	V_{IN} rising		4.2	4.5	V
		V_{IN} falling		3.7	4	V
I_Q	Quiescent current	$V_{IN} = 4.5V$ to $36V$, $V_{EN} \geq 2V$, $I_{OUT} = 0.1mA$, $V_{OUT} = 8V$, GND current		0.6	1	mA
I_{SD}	Shutdown current	EN = GND, GND current		2.5	5	μA
I_{OP}	Operating current	$V_{EN} \geq 2V$, $I_{OUT} \leq 400mA$, $V_{OUT} = 8V$, GND current			5	mA
VCC						



V_{CC}	Internal regulator output	$V_{IN} = 5.5V \text{ to } 36V, I_{CC} = 0mA$	4.5	V
I_{CC_MAX}	Internal regulator current limit		15 70	mA
LOGIC INPUTS				
V_{IL}	Logic input low level	EN and $\overline{CS_EN}$	0.7	V
V_{IH}	Logic input high level	EN and $\overline{CS_EN}$	2	V
I_{CS_EN}	Input current into $\overline{CS_EN}$	$\overline{CS_EN} = 5V, V_{EN} \geq 2V$	10	μA
I_{EN}	Leakage current into EN pin	$V_{EN} \leq 36V$	15	μA
R_{EN}	Enable pull-down resistor	$V_{EN} \leq 36V$	500	k Ω
OUTPUT PERFORMANCE				
$V_{OUT}^{(2)}$	Output accuracy in LDO mode	$36V \geq V_{IN} \geq V_{OUT} + 1.5V$ and $V_{IN} \geq 4.5V, I_{OUT} = 1mA \text{ to } 400mA$	-2 2	%
R_{on}	On-resistance in power switch mode	$I_{OUT} = 100mA$	5	Ω
$\Delta V_{OUT(\Delta V_{IN})}$	Output voltage line regulation	$36V \geq V_{IN} \geq V_{OUT} + 1.5V$ and $V_{IN} \geq 6V, I_{OUT} = 10mA$, voltage variation on FB	10	mV
$\Delta V_{OUT(\Delta I_{OUT})}$	Output voltage load regulation	$I_{OUT} = 1mA \text{ to } 400mA$, voltage variation on FB	20	mV
V_{DO}	Output dropout voltage	$I_{OUT} = 100mA$	500	mV
I_{OUT}	Output current range	V_{OUT} in regulation	0 400	mA
PSRR ⁽¹⁾	Power supply rejection ratio	$I_{OUT} = 100mA, C_{OUT} = 2.2\mu F, f = 10Hz$	70	dB
R_{OUT}	Pull down resistor for OUT	EN = GND	50	k Ω
CURRENT SENSE				
I_{OUT}/I_{CS}	OUT to CS current sense ratio	$V_{IN} = 4.5V \text{ to } 36V, I_{OUT} = 1mA \text{ to } 400mA$	198	
M_{CS}	Current sense ratio accuracy	$100mA \leq I_{OUT} \leq 400mA$	-3 3	%
		$50mA \leq I_{OUT} < 100mA$	-5 5	%
		$5mA \leq I_{OUT} < 50mA$	-10 10	%
		$I_{OUT} = 4mA$	-15 15	%
		$I_{OUT} = 3mA$	-20 20	%
		$I_{OUT} = 2mA$	-25 25	%
		$I_{OUT} = 1mA$	-50 50	%
I_{CS_LK}	CS leakage current	EN = GND, $T_A = 25^\circ C$	2	μA
V_{CS_OCL}	Current sense voltage in over current limit fault	When device is in over current limit	2.4 2.55 2.65	V



V _{CS_TSD}	Current sense voltage in thermal shutdown fault	When device is in thermal shutdown	2.7	2.85	3	V
V _{CS_STB}	Current sense voltage in short to battery fault	When device detects short to battery fault	3.05	3.2	3.3	V
I _{CS_FT}	Current sense fault condition current	When device is in OCL, TSD or STB fault	3.3			mA
CURRENT LIMIT						
I _{OUT} /I _{LIM}	OUTX to ILIM current ratio	V _{IN} = 4.5V to 36V, I _{LIM} = 1mA to 400mA	198			
M _{LIM}	Current limit accuracy	V _{IN} = 4.5V to 36V, 100mA ≤ I _{ILIM} ≤ 400mA	-5		5	%
		V _{IN} = 4.5V to 36V, 50mA ≤ I _{ILIM} < 100mA	-8		8	%
I _{LIM_MAX}	Maximum current limit	ILIM = GND	400	500	550	mA
I _{LIM_LK}	ILIM leakage current	EN = GND, T _A = 25°C			2	μA
V _{LIM}	Current limit threshold	Voltage on ILIM pin when device enters current limit	1.233			V
FEEDBACK						
V _{FB}	Reference voltage for FB	Device is in LDO mode	1.233			V
M _{FB}	Reference voltage accuracy	Device is in LDO mode	-2		2	%
I _{FB}	Leakage current into FB pin				130	nA
FAULTS						
V _{STB_TH}	Short to battery fault detection threshold	V _{OUT} – V _{IN} , check during turn-on sequence	-500	-55	110	mV
I _{REV}	Reverse current protection threshold	Device is in LDO mode or power switch mode	-100	-40	-1	mA
I _{REV_LK}	Reverse leakage current	-40V ≤ V _{IN} ≤ 0V, reverse current to V _{IN}	0.1			mA
T _{SD}	Thermal shutdown threshold	Junction temperature rise	175			°C
T _{SD_HYS}	Thermal shutdown hysteresis		15			°C
V _{ERR_OL}	Low effective $\overline{ERR}$ voltage	I _{SINK} = 5mA, $\overline{ERR}$ is low	0.4			V
I _{ERR_LK}	$\overline{ERR}$ open-drain leakage current	$\overline{ERR}$ high impedance, 5V pull-up voltage	1			μA
TIMING						
t _{d_CS_EN_R} ⁽¹⁾	Current-sense delays from the rising edge of $\overline{CS_EN}$	V _{EN} ≥ 2V, $\overline{CS_EN}$ rises from 0V to 5V	10			μs



$t_{d_CS_EN_F}^{(1)}$	Current-sense delay from the falling edge of $\overline{CS_EN}$	$V_{EN} \geq 2V$, $\overline{CS_EN}$ falls from 5V to 0V	10	μs
t_{RC_BLK}	Reverse current blanking time	Blanking time for reverse current protection after power up, rising edge of enable and OCL is released.	16	ms
$t_{RC_DGT}^{(1)}$	Reverse current (short to battery) shut down deglitch time	Delay to shut down the device when it detects negative current on pass elements. $I_{OUT} = -200mA$ (typ.), $T_A = 25^\circ C$	5	μs
t_{STB_BLK}	STB blanking time and detection window	STB blanking time and detection window after EN is pulled high	16	ms
t_{STB_DGT}	STB deglitch time	Time counting from STB release to $STB_STAT=0$	16	ms
$t_{HICCUP}^{(1)}$	Hiccup off timer (for auto-retry version only)		30	ms

(1) Guarantee by Design; not production tested.

(2) Not consider external feedback resistor's accuracy



8.6 Typical Characteristics

$V_{IN} = 14V$, $V_{OUT} = 8.5V$, unless otherwise noted.




Figure 8-1 Quiescent current vs output current






Figure 8-2 Shutdown current vs ambient temperature



$I_O = 0.1mA$

Figure 8-3 Quiescent current vs ambient temperature



$I_O = 10mA$

Figure 8-4 FB voltage vs ambient temperature




Figure 8-5 Dropout voltage vs output current




Figure 8-6 Current limit vs ambient temperature



Figure 8-7 Current sense ratio vs output current
(I_{OUT}/I_{CS})

Figure 8-8 Current sense voltage at CL vs temperature




Figure 8-9 Current sense voltage at TSD vs temperature




Figure 8-10 Current sense voltage at STB vs temperature


The block diagram illustrates the control system for the DC-DC converter. Key components and their interconnections include:

- Power Stage:** The input voltage V_{IN} passes through a reverse-blocking FET and a Pass FET to the output OUT . A Reverse current block is connected to the input side, and a diode is connected to the output side.
- Current Sensing:** A Current sense block is connected to the output of the Pass FET. Its output is connected to the inverting input of a comparator.
- Feedback and Limiting:** The feedback signal FB is connected to the non-inverting input of the comparator. The comparator's output is connected to the gate of the Pass FET. A Current Limit block is also connected to the non-inverting input of the comparator.
- Logic and Protection:** The Logic and protection block receives inputs from V_{IN} (UVLO), TSD , and the Current sense block. It outputs control signals OCL , STB , and RCP to the Current sense and multiplexing block.
- Control and Multiplexing:** The Current sense and multiplexing block receives inputs from CS_EN , CS , and $ILIM$. It outputs signals to the Current sense block and the Logic and protection block.
- Voltage Regulation:** A VCC Regulator block is connected to V_{IN} and VCC .

Figure 9-1 Functional Block Diagram



10 Timing Sequence



/ERR pin is pulled up by external power supply.

Figure 10-1 Timing Sequence for Start-up, Latch-off and Auto-retry

11 Feature Description

11.1 Overview

The SC71701Q is a single-channel low-dropout regulator (LDO) family, designed to operate for a wide input voltage range from 4.5-V to 36-V (40-V load dump capability). Capable to supply 400-mA per channel, SC71701Q provides full protection and diagnostics of automotive off-board loads and applications. In addition, 1.5-V to 22-V output voltage range and configurable power switch mode make SC71701Q very flexible. The current limit is also adjustable through ILIM pin.

Through implementing CS pin, SC71701Q is able to report accurate output current information. The CS pin is also used to report faults of open-circuit, Over Current Limit (OCL), Short Circuit Protection (SCP), Short-to-Battery (STB), Reverse Current Protection (RCP) and thermal shutdown (TSD) to MCU by pulling up its voltage to different level.

The devices integrate Back-to-Back (B2B) FET structure, which eliminates the need of extra input diode. The internal diode between OUT and GND provides inductive clamp protection in case of inductive loads during shut-down.

11.2 Fault Detection and Diagnostics

SC71701Q integrates both analog pin CS and digital pin ERR to diagnose and report faults in different operating conditions.

The CS pin is to be either precise output current sense, or full diagnostics of different faults in relevant conditions. Before entering current limit, the CS pin sources out current which is linearly proportional to the output current. With resistors R_{SNS} on CS pin, the CS's voltage is also proportional to the load current. After device enters current limit mode, CS pin's voltage is clamped to V_{CS_OCL} .

When device enters thermal shutdown mode or short to battery (STB)/Reverse current protection (RCP) mode, the CS pin's voltage is set to the fault voltage level V_{CS_TSD} and V_{CS_STB} , respectively. Refer to **Figure 11-1** for detailed demonstration of SC71701Q's current sense, fault detection and diagnostics.




Figure 11-1 Current-sense Output and Its Multiplexing

11.2.1 Current Sense and Multiplexing

In linear current sense band, before device enters current limit, CS pin output current is proportional to the output current at the OUT with a factor of 1/198. A current sense resistor R_{SNS} , must be tied between CS and GND to generate current sense voltage to MCU's ADC. To make current sense loop stable, a 1- μ F high quality ceramic capacitor needs to be used and is parallel to R_{SNS} . Refer to **Figure 11-2** for current sense configuration. **Equation 1** can be used to calculate the voltage generated at CS pin.




Figure 11-2 Current Sense Configuration

$$V_{CS} = I_{CS} \times R_{SNS} \quad (1)$$

In **Equation 1**, the relationship between CS current output I_{CS} and output current I_{OUT} is:

$$I_{CS} = \frac{I_{OUT}}{198} \quad (2)$$

To avoid overlap between linear current sense band and short circuit and current limit band, **Equation 3** can be used to determine the R_{SNS} 's maximum value R_{SNS_MAX} .

In equation:



- 198 is the output current to CS output current ratio;
- 2.4V is the minimum possible voltage at the CS pin when device is operating in overcurrent limit;
- I_{OUT_MAX} is the maximum possible output current in normal operation.

$$R_{SNS_MAX} = \frac{198 \times 2.4V}{I_{OUT_MAX}} \quad (3)$$

11.2.2 Over Current Limit and Short Circuit Protection

SC71701Q devices integrates current limit to protect the down-streaming loads from short circuit. The current limit threshold can be programmed through an external resistor R_{ILIM} on ILIM pin. The voltage on ILIM pin is compared with the internal voltage reference. When the threshold is exceeded, the current limit is triggered. The output current of the channel continues to remain on but is limited.

In current limit operation, the $\overline{ERR}$ pin asserts low and the according CS pin's voltage is pulled up to the current limit band, i.e. 2.4V to 2.65V as what has been demonstrated in **Figure 11-1**. Therefore, the $\overline{ERR}$ and CS pin can be used to report fault. The MCU should monitor device's pins and turn off relevant channel by pulling EN low. If the current limit persists, die temperature may rise high. Thermal shutdown then can be triggered to further protect the device.

11.2.3 Short-to-battery Fault Detection

Shorting the output to the battery because of a fault in an off-board system is possible. SC71701Q provides short-to-battery fault detection through comparing the voltage between the OUT pin and VIN pin before the LDO switch is turning on. When the device is enabled on the rising edge of the EN pin, VCC UVLO releasing or during the exiting of the thermal shutdown, a 15-ms(typ.) short-to-battery fault detection window starts. In the detection window if at any moment the device detects the short-to-battery fault, short-to-battery fault is triggered. The device then latches off its LDO switch, or starts auto-retry cycles, depending on the default fault logic setting. In addition, the $\overline{ERR}$ pin is asserted low and the associated CS pin voltage is pulled up internally to short-to-battery and reverse current band i.e. 3.05V to 3.3V. **Figure 11-3** shows detailed short-to-battery detection mechanism.




Figure 11-3 Short-to-battery Detection Window

If the fault condition is removed, for latch-off version (SC71701Q), the device needs to toggle EN or recycle the VIN in order to recover from latched off state.

11.2.4 Auto-retry Logic (For SC71701AQ only)

The customer option SC71701AQ provides auto-retry feature which restarts the device automatically without EN or VIN toggle, after short-to-battery and reverse current failure is cleared. **Figure 11-4** describes detailed mechanism of auto-retry.

In order to prevent failed short-to-battery detection when there is large inductance on output cable, a signal STB_STAT and STB deglitch time t_{STB_DGT} are introduced. STB_STAT is pulled high when $V_{OUT}-V_{IN}$ is higher than V_{STB_TH} . At the end of STB detection window t_{STB_BLK} , STB is detected and $\overline{ERR}$ is asserted low. After that, a 30-ms(typ.) hiccup off timer t_{HICCUP} starts. If STB is cleared ($V_{OUT}-V_{IN}$ is lower than V_{STB_TH}) early so that STB_STAT is pulled low with a deglitch time t_{STB_BLK} before hiccup off timer t_{HICCUP} ends, device restarts after a STB detection window t_{STB_BLK} and $\overline{ERR}$ recovers.

The **Figure 11-5** shows another example. If STB is cleared ($V_{OUT}-V_{IN}$ is lower than V_{STB_TH}) late so that STB_STAT is pulled low with a deglitch time t_{STB_BLK} after hiccup off timer t_{HICCUP} ends, another hiccup off timer starts. If at the end of the last hiccup off time the STB_STAT is low, the device restarts after a STB detection window t_{STB_BLK} .




Figure 11-4 Auto-retry Mechanism_1




Figure 11-5 Auto-retry Mechanism_2

11.2.5 Reverse Current Protection

Series inductance and the output capacitor can produce L-C ringing during power up or recovery from current limit, which introduces output voltage that temporarily exceeds the input voltage. There is a 15-ms(typ.) t_{RC_BLK} reverse current blanking time to filter this ringing.

11.2.6 Thermal Shutdown

The device integrates thermal shutdown feature in order to protect the device from overheat. If the junction temperature rises above 175-°C(typ.) T_{SD} threshold, the LDO switch is turned off. After junction temperature decreases by T_{SD_HYS} , the device tries to start up again. The CS's voltage is pulled up between 2.7-V and 3.3V when device is in thermal shutdown.

It should be noted that thermal shutdown is designed to protect device from overload conditions and is not intended to replace proper heat-sink. Continuously running the device into thermal shutdown state degrades device long-term reliability.

11.3 Integrated Reverse Polarity Protection

The devices integrate Back-to-Back (B2B) FET structure, which implements a reverse connected PMOS in series of pass FET. This structure blocks reverse current during reverse input polarity and short-to-battery failures, and eliminates the need of input diode, which helps save BOM cost and solution size. **Figure 11-6** describes simplified B2B structure.




Figure 11-6 Back-to-Back FET Structure

11.4 Integrated Inductive Clamp

After output is turned off, the cable inductance continuous to source the current output of the device. In order to provide robust operation and protect the device, SC71701Q integrates an inductive clamp to help dissipate the inductive energy stored in cable lines. This structure is achieved by placing an internal diode between OUT and GND pins with 400-mA DC current capability.

11.5 Under Voltage Lock-out

Device integrates input under voltage lock-out feature to protect the device from insufficient input supply. There is about 500-mV(typ.) hysteresis to help filter input ringing during and after start-up.

11.6 Enable and Disable

SC71701Q integrates EN pins to provide user-programmable enable and disable function for relevant output channel. EN pins have 500-k Ω pull-down resistance. Once EN is pulled high, the current into EN pins is limited below 10- μ A (max.).



Table 1 Fault Table

Fault Mode	V _{CS}	ERR	LDO Switch output	Latch Version	Auto-retry Version
Open load	$\frac{I_{OUT} \times R_{SNS}}{198}$	HIGH	Enabled	No	No
Normal		HIGH	Enabled	No	No
Heavy load		HIGH	Enabled	No	No
Short-circuit or current limit	2.4 to 2.65V	LOW	Enabled	No	No
Thermal shutdown	2.7 to 3V	LOW	Disabled	No	No
Output short-to-battery	3.05 to 3.3V	LOW	Disabled	Latched	Auto Retry
Reverse current	3.05 to 3.3V	LOW	Disabled	Latched	Auto Retry

11.7 FB and Output Voltage Setting

Output voltage can be adjusted externally through feedback divider network on FB pin, as what has been shown in **Figure 11-7**. In LDO mode, output voltage can be adjusted from 1.5-V to 22-V by selecting feedback divider resistance from **Equation 4**. The SC71701Q can also be used as a current-limited switch by connecting the FB pin to the GND pin (switch mode) to fully turn on LDO switches. The output voltage of switch mode in no load is same as input voltage, and can be above 22-V.

$$1.233 = \frac{R_2}{R_1 + R_2} \cdot V_{OUT} \quad (4)$$




Figure 11-7 Feedback Network

12 Application Information

The SC71701Q, as a single -channel low-dropout regulator (LDO) family, is specifically designed for automotive off-battery power applications, such as automotive antenna, camera and microphones, providing reliable and accurate current sense, current limit and fault diagnostics functionalities.

Figure 6-1 demonstrates typical application circuits of SC71701Q.

12.1 Design Procedure

The following sections describe detail design procedure for parameters listed in **Table 3** as an example.

Table 2 Example Design Parameters

PARAMETERS	VALUE EXAMPLE
Input voltage range	9V to 16V, battery supplied
Output voltage	8.5V for OUT
Maximum output current	100mA
Output current limit	200mA

12.1.1 Input Capacitor

Input decoupling capacitors are needed for the device, depending on different applications. Typical value for input capacitor is 10μF. There are mainly considerations in capacitor selections.

The first one is voltage rating. The voltage rating for the capacitor should always be larger than application's maximum input voltage. In terms of automotive battery supplied application, voltage rating higher than 36V is usually needed.

When one channel is configured in switch mode and another channel is suddenly short to GND, input voltage can have a temporary drop. If the input capacitor capacitance is not enough, voltage drop can result in reverse current protection triggered for the switch mode channel. This is especially more severe if the channel in switch mode has very light load. Increase capacitor's actual capacitance, or add bulk capacitor can help reduce the voltage drop and prevent false reverse current protection triggering.

In this design example, a 10μF rating capacitance, X7R/50V, automotive capacitor is selected.

12.1.2 Output Capacitor

The device needs output capacitor to make loop stable. The output capacitance range is between 2.2μF to 100μF with ESR from 0Ω to 5Ω. It is recommended to select a low ESR

capacitor with higher capacitance rating if load transient performance is important.

In addition, a 100nF high quality ceramic capacitor is recommended to be used to increase PSRR at high frequency band.

If any line inductance at output lines, output capacitors must be placed close to IC so that loop stability is not disturbed by output inductance in lines.

In this design case, one 100nF/X7R/50V automotive ceramic capacitor and one 10μF/X7R/50V automotive ceramic capacitor are used for each output channel.

12.1.3 Current Sense Resistor Selection

The device reports output current through CS pin. CS pins' output current are proportional to the output current at the OUT with a factor of 1/198. Therefore, an output resistor R_{SNS} must be used between CS and GND to convert current to voltage for external ADC to sample. Refer to **Section 12.2.1** for detailed R_{SNS} calculation.

In this example, maximum output current is 100mA. Therefore, the maximum R_{SNS} is:

$$R_{SNS_MAX} = \frac{198 \times 2.4V}{100mA} = 4.752k\Omega$$

The nearest resistor value of 4.7kΩ for R_{SNS} is selected.

Table 4 lists current sense accuracy across temperature.

Table 3 Output Current Sense Accuracy Summary

OUTPUT CURRENT	SENSE ACCURACY
1mA	±50%
2mA	±25%
3mA	±20%
4mA	±15%
5mA ≤ I _{OUT} < 50mA	±10%
50mA ≤ I _{OUT} < 100mA	±5%
100mA ≤ I _{OUT} ≤ 400mA	±3%

12.1.4 Current Limit Resistor Selection

The device reports output current limit status through ILIM pin. ILIM pins' output current are proportional to the output current at the OUT pins and is internally connected to a current-limit comparator referenced to 1.233 V. Therefore, a resistor R_{LIM} could be selected between ILIM and GND to program the current limit of OUT pin. The internal current limit of the device is set by shorting the ILIM pin to ground.

In this example, output current limit is 200mA. Therefore, the R_{LIM} is:



$$R_{ILIM} = \frac{198 \times 1.233V}{200mA} = 1.220k\Omega$$

The nearest resistor value of 1.2kΩ is selected.



12.2 Application Curves

$V_{IN} = 14V$, $V_{OUT} = 8.5V$, unless otherwise noted.




Figure 12-1 Power Up ($V_{IN} = 14V$, $I_O = 100\text{ mA}$)




Figure 12-2 Power Down ($V_{IN} = 14V$, $I_O = 100\text{ mA}$)




Figure 12-3 $I_{OUT} = 10\text{-mA}$ to 200-mA Load Transient




Figure 12-4 $I_{OUT} = 200\text{-mA}$ to 400-mA Load Transient




Figure 12-5 9-V to 16-V Line Transient ($I_{OUT} = 50\text{mA}$)




Figure 12-6 Current Sense Enable and disable




Figure 12-7 Current Limit




Figure 12-8 Thermal Shutdown Protection




Figure 12-9 Short-to-battery Protection(Latch)




Figure 12-10 Short-to-battery Protection(Retry)




Figure 12-11 Reverse Current Protection(Latch)




Figure 12-12 Reverse Current Protection(Retry)



13 Layout Guide

For the layout of SC71701Q device, the layout guide recommends are as followed:

- Place any of the capacitors on the same side of the PCB from where the regulator is installed.
- Place every capacitor as close as possible to the device.
- Put some via holes surrounding the device to enhance the thermal performance.






Figure 13-1 PCB Layout Example



14 PACKAGING INFORMATION




SECTION B-B

eTSSOP16L POD

SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	-	-	1.20
A1	0.00	-	0.15
A2	0.90	1.00	1.05
A3	0.39	0.44	0.49
b	0.20	-	0.28
b1	0.19	0.22	0.25
c	0.13	-	0.17
c1	0.12	0.13	0.14
D	4.90	5.00	5.10
E	6.20	6.40	6.60
E1	4.30	4.40	4.50
e	0.65BSC		
L	0.45	-	0.75
L1	1.00BSC		
θ	0	-	8°

U/F Size(mm)	D2	E2
91*118	2.80REF	2.10REF


Unit: mm



SYMBOL	TYPICAL
S	4.55
Q	5.80
R	1.50
T	0.45
Z	0.65 BSC
eX	2.10
eY	2.80

eTSSOP16L Land Pattern

Unit: mm




SOLDER PASTE EXAMPLE
BASED ON 0.125mm THICK STENCIL
SCALE: 10X

Unit: mm


STENCIL THICKNESS	SOLDER STENCIL OPENING
0.1	2.75 X 3.97
0.125	2.46 X 3.55 (SHOWN)
0.15	2.25 X 3.24
0.175	2.08 X 3.00



15 TAPE AND REEL INFORMATION

Carrier Tape

Item	W	P	A0	B0	K0	t	Pin1 Quadrant
Size (mm)	12.0 ± 0.1	8.0 ± 0.1	6.8 ± 0.1	5.4 ± 0.1	1.3 ± 0.1	0.3 ± 0.05	Q1

REEL

Item	A	W1	T
Size (mm)	330 ± 1	$12.4 +1/-0$	1.5 ± 0.3



Important Notice and Disclaimer

Southchip Semiconductor Technology (Shanghai) Co., Ltd. and its subsidiaries (“**SOUTHCHIP**”) provides technical and reliability data (including datasheets), design resources (including reference designs, software), application or other design advice and other resources (“**Resources**”) “**AS IS**” AND WITH ALL FAULTS.

The Resources are intended for skilled developers designing with SOUTHCHIP’s products. SOUTHCHIP may provide but **DISCLAIMS WARRANTY FOR** SOUTHCHIP’s technical support or design services for the customers. Customers are solely responsible for (1) selecting and using the appropriate SOUTHCHIP’s products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. SOUTHCHIP **DISCLAIMS RESPONSIBILITY FOR** any claims, damages, costs, losses, liabilities arising out of Customers’ use of the Resources.

SOUTHCHIP’s sample products are provided “**AS IS**” and only for purposes of designing, validating and testing. SOUTHCHIP reserves the right to make changes, corrections, enhancements, modifications and improvements to SOUTHCHIP’s products and/or to the Resources at any time without notice. Customers shall, prior to, mass producing, using or distributing any products of their own that incorporate SOUTHCHIP’s products, obtain the latest relevant information on SOUTHCHIP’s products and thoroughly test such products for purposes of mass production, quality and safety. Use of SOUTHCHIP’s products without a safety design is fully at the risk of Customers, subject only to applicable laws and regulations governing limitations on product liability.