

Description

Chinasound Micro Speaker 40mm diameter, Round metal frame, 5mm height, type C (coil with paper frame)-8ohm rated impedance, NdFeB magnet, 1W rated power - type 2, Al plated Mylar cone, 600 Hz rated frequency, RoHS compliant

- ◆ RoHS compliant
- ◆ Water-proof IP65 in the front
- ◆ Small size

Picture



Frequency Response Curve Tested by CLIO



Specification

- Rated Impedance
- Rated Power
- Max. Power
- Resonant Frequency
- Frequency Range
- Sound Pressure Level
- Operating Temperature
- Storage Temperature
- Termination
- Construction Materials

- Description
- Case
- Diaphragm


- Weight (Typical)
- Reliability

- *Buzzes & Rattles
- *Load Test
- *High Temperature
- *Low Temperature
- *Humidity
- *Thermal Shock
- *Vibration

Warranty

* All specifications must be satisfied after the test (Recovery: 2 to 4 hrs of recovery under the standard condition after the removal from test chamber).

Dimensions (Unit: mm)



All specifications are subject to change without notice

Composed by: Chrissy D/190729

Checked by: James Z/190729

Approved by: William W /190729



CHANGZHOU CHINASOUND ELECTRONICS CO., LTD.

Tel: +86-519-86182518 Fax: +86-519-86182519

<http://www.chinasound.com>

email: market@chinasound.com

Revisions History

Version Number	Description	Name	Date
SP1.10.074-A0	Original, CMS40R5C-8N1-2A600R	Chrissy Deng	2016-07-04
SP1.10.074-A1	Add the description of the waterproof rating	Chrissy Deng	2019-07-29