

SOLUTIONS WHICH CONNECT



MAS-CON

- Two different Pitches (2.54mm & 3.96mm)
- Different AWG sizes
- For flat ribbon cable or single-wire cable
- Polarized types available



LAT-CON 2,54mm

- Female and Male connectors
- For flat ribbon cable
- For Wire 2 Wire and Wire 2 Board connections
- Strain Reliefs available



LAT-CON 1,27mm

- Very compact
- For Board 2 Board and Wire 2 Board connections
- 100% protection against mismatching.
- Contact overlapping 2,50mm



HI-CON

- According DIN 41612 / DIN EN 60 603-2
- Standardized connectors
- Female and Male connectors
- For Board 2 Board and Wire 2 Board connections



BOARD-CON

- Female and Male connectors
- Different pitches
- For PCB stacking or other direct connections
- High quantity of different forms available



CRIMP-CON

- Female and Male connectors
- Different pitches
- For Wire 2 Wire and Wire 2 Board connections
- Comparable alternatives to competitor products



JUMPER SWITCHES

- ON/OFF, CHANGEOVER and CENTRE-OFF
- For Board 2 Board and Wire 2 Board connections
- No exposed bare „parking pins“ required
- Reflow solderable



TERMINAL BLOCKS

- Different pitches
- Different types
- Female and Male connectors
- Screwable versions available

